

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

Easy Glass Coat

**Product no.**

-

**REACH registration number**

Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Coating

**Uses advised against**

-

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

**Company and address**

Blue & Green AB  
Stenorsvägen 52  
261 44 Landskrona  
Sweden  
Tfn: +46 418 399000  
Fax: +46 418 13199  
www.blueandgreen.se

**E-mail**

info@blueandgreen.se

**SDS date**

2020-10-06

**SDS Version**

1.0

### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Flam. Liq. 3; H226

See full text of H-phrases in section 2.2.

### 2.2. Label elements

**Hazard pictogram(s)****Signal word**

Warning

**Hazard statement(s)**

Flammable liquid and vapour. (H226)

**Precautionary statements****General**

If medical advice is needed, have product container or label at hand. (P101).  
Keep out of reach of children. (P102).

According to EC-Regulation 2015/830

<b>Prevention</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210).
<b>Response</b>	In case of fire: Use alcohol-resistant foam/carbonic acid/powder/water mist/carbon dioxide/dry sand to extinguish. (P370+P378).
<b>Storage</b>	Store in a well-ventilated place. Keep cool. (P403+P235).
<b>Disposal</b>	Dispose of contents/container to an approved waste disposal plant. (P501).

**Identity of the substances primarily responsible for the major health hazards**

Not applicable

**Additional labelling**

Contains 1,2-benzisothiazol-3(2H)-one 1,2-benzisothiazolin-3-one . May produce an allergic reaction. (EUH208).

**Unique formula identifier (UFI)**

HCEW-S91A-X10A-7VP5

**2.3. Other hazards**

Not applicable

**Additional warnings**

Not applicable

**VOC (volatile organic compound)**

Not applicable

**SECTION 3: Composition/information on ingredients**

**3.1/3.2. Substances/Mixtures**

NAME:	propan-2-ol
IDENTIFICATION NOS.:	CAS-no: 67-63-0 EC-no: 200-661-7 REACH-no: 01-2119457558-25 Index-no: 603-117-00-0
CONTENT:	5 - <10%
CLP CLASSIFICATION:	Flam. Liq. 2, STOT SE 3, Eye Irrit. 2 H225, H319, H336
NOTE:	O

(\* ) O = Organic solvent See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

**Other information**

ATEmix(oral) > 2000  
Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 0.4 - 0.6

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

**Inhalation**

Bring the person into fresh air and stay with him/her.

**Skin contact**

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water.

**Eye contact**

Flush eyes with plenty of water (20-30°C) and continue until irritation stops.

**Ingestion**

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

**Burns**

Rinse with water until the pain stops then continue to rinse for a further 30 minutes.

**4.2. Most important symptoms and effects, both acute and delayed**

Nothing special

According to EC-Regulation 2015/830

#### 4.3. Indication of any immediate medical attention and special treatment needed

Nothing special

#### Information to medics

Bring this safety data sheet.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

#### 5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

#### 6.2. Environmental precautions

No specific requirements.

#### 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

#### 6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Avoid static electricity. Protect electrical equipment in accordance with current standards. Do not use spark-forming tools.

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms.

See section on 'Exposure controls/personal protection' for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

#### Storage temperature

Room temperature 18 to 23°C

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### OEL

propan-2-ol

Long-term exposure limit (8-hour TWA reference period): 400 ppm | 999 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 500 ppm | 1250 mg/m<sup>3</sup>

##### DNEL / PNEC

DNEL (propan-2-ol): 319 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 89 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 26 mg/kg bw/d

According to EC-Regulation 2015/830

Exposure: Oral  
Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 888 mg/kg bw/d  
Exposure: Dermal  
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (propan-2-ol): 500 mg/m<sup>3</sup>  
Exposure: Inhalation  
Duration of Exposure: Long term – Systemic effects - Workers

PNEC (propan-2-ol): 552 mg/kg dw  
Exposure: Marine water sediment

PNEC (propan-2-ol): 140.9 mg/l  
Exposure: Freshwater

PNEC (propan-2-ol): 28 mg/kg dw  
Exposure: Soil

PNEC (propan-2-ol): 140.9 mg/l  
Exposure: Marine water

PNEC (propan-2-ol): 140.9 mg/l  
Exposure: Intermittent release

PNEC (propan-2-ol): 2251 mg/l  
Exposure: Sewage Treatment Plant

PNEC (propan-2-ol): 552 mg/kg dw  
Exposure: Freshwater sediment

## 8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Observe general occupational hygiene standards.

### Exposure scenarios

There is no appendix to this safety data sheet.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Ensure emergency eyewash and -showers are clearly marked.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

### Measures to avoid environmental exposure

No specific requirements.

### Individual protection measures, such as personal protective equipment



#### Generally

Use only CE marked protective equipment.

#### Respiratory Equipment

No specific requirements.

#### Skin protection

No specific requirements.

#### Hand protection

Nitrile rubber

Breakthrough time: > 480 minutes (Class 6)

#### Eye protection

No specific requirements.

According to EC-Regulation 2015/830

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Form	Liquid
Colour	Transparent
Odour	None
Odour threshold (ppm)	No data available.
pH	6
Viscosity (40°C)	No data available.
Density (g/cm <sup>3</sup> )	0.99

#### Phase changes

Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

#### Data on fire and explosion hazards

Flash point (°C)	60
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

#### Solubility

Solubility in water	Soluble
n-octanol/water coefficient	No data available.

### 9.2. Other information

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

### 10.3. Possibility of hazardous reactions

Nothing special

### 10.4. Conditions to avoid

Avoid static electricity.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Substance: propan-2-ol  
Species: Rat  
Test: LD50  
Route of exposure: Oral  
Result: 5840 mg/kg

Substance: propan-2-ol  
Species: Rat  
Test: LC50  
Route of exposure: Inhalation  
Result: >25 mg/l, 6h ånga

Substance: propan-2-ol  
Species: Rabbit  
Test: LD50  
Route of exposure: Dermal  
Result: 13900 mg/kg

According to EC-Regulation 2015/830

**Skin corrosion/irritation**

No data available.

**Serious eye damage/irritation**

No data available.

**Respiratory or skin sensitisation**

No data available.

**Germ cell mutagenicity**

No data available.

**Carcinogenicity**

No data available.

**Reproductive toxicity**

No data available.

**STOT-single exposure**

No data available.

**STOT-repeated exposure**

No data available.

**Aspiration hazard**

No data available.

**Long term effects**

Nothing special

**SECTION 12: Ecological information**

**12.1. Toxicity**

Substance: propan-2-ol

Species: Fish

Test: LC50

Duration: 96h

Result: >100 mg/l

Substance: propan-2-ol

Species: Daphnia

Test: LC50

Duration: 48h

Result: >100 mg/l

Substance: propan-2-ol

Species: Algae

Test: EC50

Duration: 72h

Result: >100mg/l

**12.2. Persistence and degradability**

Substance

propan-2-ol

Biodegradability

Yes

Test

No data available

Result

No data available

**12.3. Bioaccumulative potential**

Substance

propan-2-ol

Potential bioaccumulation

No

LogPow

0.05

BCF

No data available

**12.4. Mobility in soil**

propan-2-ol: Log Koc= 0.117995, Calculated from LogPow (High mobility potential.).

**12.5. Results of PBT and vPvB assessment**

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

**12.6. Other adverse effects**

Nothing special

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Product is covered by the regulations on hazardous waste.

**Waste**

EWC code

-

**Specific labelling**

Not applicable

**Contaminated packing**

Contaminated packaging must be disposed of similarly to the product.

**SECTION 14: Transport information**

**14.1 – 14.4**

According to EC-Regulation 2015/830

This product is within scope of the regulations of transport of dangerous goods.

**ADR/RID**

<b>14.1. UN number</b>	1993
<b>14.2. UN proper shipping name</b>	FLAMMABLE LIQUID, N.O.S.
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	III
<b>Notes</b>	-
<b>Tunnel restriction code</b>	D/E

**IMDG**

<b>UN-no.</b>	1993
<b>Proper Shipping Name</b>	FLAMMABLE LIQUID, N.O.S.
<b>Class</b>	3
<b>PG*</b>	III
<b>EmS</b>	F-E, S-E
<b>MP**</b>	No
<b>Hazardous constituent</b>	-

**IATA/ICAO**

<b>UN-no.</b>	1993
<b>Proper Shipping Name</b>	FLAMMABLE LIQUID, N.O.S.
<b>Class</b>	3
<b>PG*</b>	III

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available

(\*) Packing group

(\*\*) Marine pollutant

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Restrictions for application**

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

**Demands for specific education**

-

**Additional information**

Not applicable

**Seveso**

Seveso III Part 1: P5c

**Biocidal reg. no.**

Not applicable

**Sources**

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.  
 The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.  
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).  
 Regulation (EC) 1907/2006 (REACH).  
 The Control of Major Accident Hazards (COMAH) Regulations 2015.

**15.2. Chemical safety assessment**

No

**SECTION 16: Other information**

**Full text of H-phrases as mentioned in section 3**

H225 - Highly flammable liquid and vapour.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

According to EC-Regulation 2015/830

**The full text of identified uses as mentioned in section 1**

-

**Additional label elements**

Not applicable

**Other**

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of physical hazards has been based on experimental data.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

**The safety data sheet is validated by**

David Löwenstein

**Date of last essential change  
(First cipher in SDS version)**

-

**Date of last minor change  
(Last cipher in SDS version)**

-