

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

Print Wash 10

**Product no.**

-

**REACH registration number**

Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Washing liquid for the graphic industry

**Uses advised against**

-

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

**Company and address**

**Blue & Green AB**  
**Stenorsvägen 52**  
**261 44 Landskrona**  
**Sweden**  
**Tfn: +46 418 399000**  
**Fax: +46 418 13199**  
**www.blueandgreen.se**

**E-mail**

info@blueandgreen.se

**SDS date**

2021-03-01

**SDS Version**

2.0

### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Flam. Liq. 2; H225  
 Asp. Tox. 1; H304  
 Skin Irrit. 2; H315  
 Eye Irrit. 2; H319  
 STOT SE 3; H336  
 Aquatic Chronic 2; H411  
 See full text of H-phrases in section 2.2.

### 2.2. Label elements

**Hazard pictogram(s)**



**Signal word**

Danger

**Hazard statement(s)**

According to EC-Regulation 2015/830

Highly flammable liquid and vapour. (H225)  
 May be fatal if swallowed and enters airways. (H304)  
 Causes skin irritation. (H315)  
 Causes serious eye irritation. (H319)  
 May cause drowsiness or dizziness. (H336)  
 Toxic to aquatic life with long lasting effects. (H411)

#### ▼ Precautionary statements

**General** If medical advice is needed, have product container or label at hand. (P101).  
 Keep out of reach of children. (P102).  
**Prevention** Wear eye protection/gloves. (P280).  
**Response** IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310).  
**Storage** Store in a well-ventilated place. Keep cool. (P403+P235).  
**Disposal** Dispose of contents/container to an approved waste disposal plant. (P501).

#### ▼ Identity of the substances primarily responsible for the major health hazards

propan-2-ol; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; cyclohexane

#### Additional labelling

Not applicable

#### Unique formula identifier (UFI)

1JFP-8Q71-W10M-2YHY

#### ▼ 2.3. Other hazards

This product contains substances that can cause chemical pneumonia if inhaled. The symptoms of chemical pneumonia may appear after several hours.

This product contains an organic solvent. Repeated or prolonged exposure to organic solvents may result in adverse effects to the nervous system and internal organs such as liver and kidneys.

#### ▼ Additional warnings

Tactile warning. If this product is sold in retail, it must be delivered with child-resistant fastening.

#### VOC (volatile organic compound)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1/3.2. Substances/Mixtures

NAME: propan-2-ol  
 IDENTIFICATION NOS.: CAS-no: 67-63-0 EC-no: 200-661-7 REACH-no: 01-2119457558-25 Index-no: 603-117-00-0  
 CONTENT: 40-60%  
 CLP CLASSIFICATION: Flam. Liq. 2, STOT SE 3, Eye Irrit. 2  
 H225, H319, H336  
 NOTE: O

NAME: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
 IDENTIFICATION NOS.: EC-no: 927-510-4 REACH-no: 01-2119475505-33  
 CONTENT: 40-60%  
 CLP CLASSIFICATION: Flam. Liq. 2, Asp. Tox. 1, Skin Irrit. 2, STOT SE 3, Aquatic Chronic 2  
 H225, H304, H315, H336, H411  
 NOTE: O

NAME: cyclohexane  
 IDENTIFICATION NOS.: CAS-no: 110-82-7 EC-no: 203-806-2 Index-no: 601-017-00-1  
 CONTENT: 0.25 - <1%  
 CLP CLASSIFICATION: Flam. Liq. 2, STOT SE 3, Skin Irrit. 2, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1  
 H225, H304, H315, H336, H400, H410 (M-acute = 1) (M-chronic = 1)  
 NOTE: O L

(\*) O = Organic solvent L = European occupational exposure limit. See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

Eye Cat. 2 Sum =  $\sum(Ci/S(G)CLi) = 4.08 - 6.12$   
 Skin Cat. 2 Sum =  $\sum(Ci/S(G)CLi) = 1.5368 - 2.3052$   
 N chronic (CAT 2) Sum =  $\sum(Ci/(M(chronic))^i * 25) * 0.1 * 10^{CATi}) = 1.85024 - 2.77536$   
 N acute (CAT 1) Sum =  $\sum(Ci/M(acute))^i * 25) = 0.03136 - 0.04704$

Detergent:  
 > 30%: ISOPROPYL ALCOHOL, ALIPHATIC HYDROCARBONS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Bring the person into fresh air and stay with him/her.

#### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water.

#### Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

#### ▼ Ingestion

Do not induce vomiting! If vomiting occurs, keep head facing down to prevent vomit entering the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should be kept under medical attention for a minimum of 48 hours.

#### Burns

Rinse with water until the pain stops then continue to rinse for a further 30 minutes.

### ▼ 4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if inhaled. The symptoms of chemical pneumonia may appear after several hours.

This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: headache, dizziness, ringing in ears, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.

Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get immediate medical advice/attention.

#### Information to medics

Bring this safety data sheet.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

### 5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

### ▼ 6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours from spilled material. Avoid direct contact with spilled substances. Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local

According to EC-Regulation 2015/830

environmental authorities. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment.

### 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

### 6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid static electricity. Protect electrical equipment in accordance with current standards. Do not use spark-forming tools.

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment. See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

#### Storage temperature

Room temperature 18 to 23°C

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### OEL

cyclohexane

Long-term exposure limit (8-hour TWA reference period): 100 ppm | 350 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 300 ppm | 1050 mg/m<sup>3</sup>

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Long-term exposure limit (8-hour TWA reference period): 500 ppm | 2085 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): - ppm | - mg/m<sup>3</sup>

propan-2-ol

Long-term exposure limit (8-hour TWA reference period): 400 ppm | 999 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 500 ppm | 1250 mg/m<sup>3</sup>

#### DNEL / PNEC

DNEL (propan-2-ol): 319 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 89 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 26 mg/kg bw/d

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 888 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (propan-2-ol): 500 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics): 300 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics): 2085 mg/m<sup>3</sup>

Exposure: Inhalation

According to EC-Regulation 2015/830

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics): 149 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics): 477 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics): 149 mg/kg bw/d

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

PNEC (propan-2-ol): 552 mg/kg dw

Exposure: Marine water sediment

PNEC (propan-2-ol): 140.9 mg/l

Exposure: Freshwater

PNEC (propan-2-ol): 28 mg/kg dw

Exposure: Soil

PNEC (propan-2-ol): 140.9 mg/l

Exposure: Marine water

PNEC (propan-2-ol): 140.9 mg/l

Exposure: Intermittent release

PNEC (propan-2-ol): 2251 mg/l

Exposure: Sewage Treatment Plant

PNEC (propan-2-ol): 552 mg/kg dw

Exposure: Freshwater sediment

## 8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Observe general occupational hygiene standards.

### Exposure scenarios

There is no appendix to this safety data sheet.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Ensure emergency eyewash and -showers are clearly marked.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

### Measures to avoid environmental exposure

Keep containment materials near the workplace. If possible, collect spillage during work.

### Individual protection measures, such as personal protective equipment



### Generally

Use only CE marked protective equipment.

### Respiratory Equipment

Recommended: A. Class 1 (low capacity). Brown

### Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene approved type 6 and Category III.

### Hand protection

4H/Barrier

According to EC-Regulation 2015/830

Breakthrough time: > 480 minutes (Class 6)

**Eye protection**

Wear safety glasses with side shields.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Form	Liquid
Colour	Green
Odour	Sharp/pungent
Odour threshold (ppm)	No data available.
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm <sup>3</sup> )	0.75

**Phase changes**

Melting point (°C)	No data available.
Boiling point (°C)	83-100
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

**Data on fire and explosion hazards**

Flash point (°C)	8
Ignition (°C)	No data available.
Auto flammability (°C)	>200
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

**Solubility**

Solubility in water	Insoluble
n-octanol/water coefficient	No data available.

**9.2. Other information**

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No data available

**10.2. Chemical stability**

The product is stable under the conditions, noted in the section "Handling and storage".

**10.3. Possibility of hazardous reactions**

Nothing special

**10.4. Conditions to avoid**

Avoid static electricity.

**10.5. Incompatible materials**

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

**10.6. Hazardous decomposition products**

The product is not degraded when used as specified in section 1.

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Acute toxicity**

Substance: cyclohexane  
 Species: Rabbit  
 Test: LD50  
 Route of exposure: Dermal  
 Result: >2000 mg/kg

Substance: cyclohexane  
 Species: Rat  
 Test: LD50  
 Route of exposure: Oral  
 Result: >5000 mg/kg

Substance: cyclohexane

According to EC-Regulation 2015/830

Species: Rat  
 Test: LC50  
 Route of exposure: Inhalation  
 Result: 14 mg/m<sup>3</sup>, 4 h

Substance: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
 Species: Rat  
 Test: LD50  
 Route of exposure: Dermal  
 Result: >2920 mg/kg

Substance: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
 Species: Rat  
 Test: LD50  
 Route of exposure: Oral  
 Result: >5840 mg/kg

Substance: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
 Species: Rat  
 Test: LC50  
 Route of exposure: Inhalation  
 Result: >23.3 mg/l, 4 h ånga

Substance: propan-2-ol  
 Species: Rabbit  
 Test: LD50  
 Route of exposure: Dermal  
 Result: 13900 mg/kg

Substance: propan-2-ol  
 Species: Rat  
 Test: LD50  
 Route of exposure: Oral  
 Result: 5840 mg/kg

Substance: propan-2-ol  
 Species: Rat  
 Test: LC50  
 Route of exposure: Inhalation  
 Result: >25 mg/l, 6h ånga

▼ **Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

No data available.

**Germ cell mutagenicity**

No data available.

**Carcinogenicity**

No data available.

**Reproductive toxicity**

No data available.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure**

No data available.

▼ **Aspiration hazard**

May be fatal if swallowed and enters airways.

**Long term effects**

This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: headache, dizziness, ringing in ears, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

## SECTION 12: Ecological information

### 12.1. Toxicity

Substance: cyclohexane  
 Species: Daphnia  
 Test: EC50  
 Duration: 48h  
 Result: 3.78 mg/l

According to EC-Regulation 2015/830

Substance: cyclohexane  
Species: Fish  
Test: LC50  
Duration: 48h  
Result: 55 mg/l

Substance: cyclohexane  
Species: Algae  
Test: EC50  
Duration: 72h  
Result: >500 mg/l

Substance: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
Species: Daphnia  
Test: NOEC  
Duration: 21 d  
Result: 0.17 mg/l

Substance: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
Species: Daphnia  
Test: EC50  
Duration: 48 h  
Result: 3 mg/l

Substance: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
Species: Fish  
Test: LC50  
Duration: 96 h  
Result: 13.4 mg/l

Substance: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
Species: Algae  
Test: EC50  
Duration: 72 h  
Result: 10-30 mg/l

Substance: propan-2-ol  
Species: Daphnia  
Test: LC50  
Duration: 48h  
Result: >100 mg/l

Substance: propan-2-ol  
Species: Fish  
Test: LC50  
Duration: 96h  
Result: >100 mg/l

Substance: propan-2-ol  
Species: Algae  
Test: EC50  
Duration: 72h  
Result: >100mg/l

### 12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
cyclohexane	No	No data available	No data available
Hydrocarbons, C7, n-alkanes, i...	Yes	No data available	No data available
propan-2-ol	Yes	No data available	No data available

### 12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
cyclohexane	No	No data available	No data available
Hydrocarbons, C7, n-alkanes, i...	No	No data available	No data available
propan-2-ol	No	0.05	No data available

### 12.4. Mobility in soil

propan-2-ol: Log Koc= 0.117995, Calculated from LogPow (High mobility potential.).

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

### 12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.  
This product contains substances, which may cause adverse long-term effects to the aquatic environment.



According to EC-Regulation 2015/830

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

#### Waste

EWC code

-

#### Specific labelling

Not applicable

#### Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

## SECTION 14: Transport information

### 14.1 – 14.4

This product is within scope of the regulations of transport of dangerous goods.

#### ADR/RID

14.1. UN number	1993
14.2. UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es)	3
14.4. Packing group	II
Notes	-
Tunnel restriction code	-

#### IMDG

UN-no.	1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Class	3
PG*	II
EmS	F-E,S-D
MP**	-
Hazardous constituent	-

#### IATA/ICAO

UN-no.	1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Class	3
PG*	II

### 14.5. Environmental hazards

-

### 14.6. Special precautions for user

-

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(\*) Packing group

(\*\*) Marine pollutant

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

-

#### Additional information

Not applicable

#### Seveso

Seveso III Part 1: P5c, E2

#### Biocidal reg. no.

Not applicable

#### Sources

According to EC-Regulation 2015/830

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.  
 The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.  
 Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.  
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).  
 Regulation (EC) 1907/2006 (REACH).  
 The Control of Major Accident Hazards (COMAH) Regulations 2015.

## 15.2. Chemical safety assessment

No

## SECTION 16: Other information

### Full text of H-phrases as mentioned in section 3

H225 - Highly flammable liquid and vapour.  
 H304 - May be fatal if swallowed and enters airways.  
 H315 - Causes skin irritation.  
 H319 - Causes serious eye irritation.  
 H336 - May cause drowsiness or dizziness.  
 H400 - Very toxic to aquatic life.  
 H410 - Very toxic to aquatic life with long lasting effects.  
 H411 - Toxic to aquatic life with long lasting effects.

### The full text of identified uses as mentioned in section 1

-

### Additional label elements

Not applicable

### Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:  
 The classification of the mixture in regard of physical hazards has been based on experimental data.  
 The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)  
 The classification of the mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)  
 It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.  
 The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.  
 A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

### The safety data sheet is validated by

Cecilia Evaldsson

### Date of last essential change (First cipher in SDS version)

2020-11-10(1.0)

### Date of last minor change (Last cipher in SDS version)

2020-11-10